

AMENDMENTS TO THE CLAIMS

1. *(original)* A method of handling an empty beverage container having opposed first and second ends of different properties, the container having an axis extending between the first and second ends, said first end defined as a bottom end of the container and said second end defined
5 as a mouth region of the container, the method comprising the step of moving the container, from a return vending machine inlet, in a direction towards an outlet thereof,

wherein the method comprises the further steps of:

- detecting by means of a video camera the container when moved in a
10 lying posture into or past a detection zone of the video camera and the manner by which the container is inserted at said inlet,
- determining whether the container is moved into the detection zone with its first end first or with its second end first, and
- either transporting the container to said outlet if it is delivered into the
15 detection zone with its first end first,
- or causing the container to be returned to the inlet if it is delivered into the detection zone with its second end first.

2. *(original)* A method according to claim 1, wherein upon return of the container to the inlet, the further step of: issuing a prompt to a return vending machine user to remove the container and reinsert it into the inlet with its first end first.

3. (*currently amended*) A method according to claim 1 [~~or~~
2], wherein the method comprises the further step of determining a most
suitable video image obtained by the video camera with a view to recognition
and identification of the container.

4. (*currently amended*) A method according to claim 1, [~~2-or~~
3,] wherein the method comprises the further steps of observing any
longitudinal markings in the video image of a container being a bottle,
emitting a signal indicating that the container fully or partly contains liquid or
5 another substance, and possibly returning the container to the user for
emptying prior to reinsertion.

5. (*original*) A method according to claim 1, wherein said
manner of insertion is related to orientation of the container.

6. (*original*) A return vending machine device for detecting empty
beverage containers to be reused or recycled, comprising a video analyser for video
image analysis of a container moved into or past a detection zone, the video
analyser being connected to a video camera, wherein said analyser has a calculator
5 component for determining, when the container moves in a lying posture into the
detection zone, whether it enters the video camera field of view with its first end
first, viz. its bottom end, or its second end first, viz. its mouth region, and wherein
the device further has a control component capable of causing the container either

to be returned to a device inlet if it is entered into the detection zone with its
10 second end first, means being provided to cause a device user to reinsert the
container with its first end first, or if it is entered into the device with its first end
first to feed it past the detection zone and onwards to a discharge station.

7. (*original*) A return vending machine device according to
claim 6, wherein a prompt is made to the device user to cause said reinsertion
of a returned container, said prompt being provided by a signaling means
signaling the need to turn returned the container so that it is inserted bottom
5 first.

8. (*currently amended*) A return vending machine device
according to claim 6 [~~or 7~~], wherein a position detector is provided, capable
of determining position and movement of the container in a viewing region of
the video camera on basis of continuous detection of position and movement
5 of the container in the video image.

9. (*currently amended*) A return vending machine device
according to claim 6, [~~7 or 8~~] wherein the video analyser includes a circuit
capable of determining, with a view to recognition and identification of a
container, a best video image of video images taken of the container.

10. (*currently amended*) A return vending machine device according to [~~anyone of claims 6—9~~] **claim 6**, when applied to a container in the form of a bottle, wherein the analyser contains an observation circuit adapted to observe any longitudinal markings in a video image of the bottle,
- 5 said observation circuit capable of emitting a signal when such markings are observed to indicate that the bottle contains fully or partly liquid or other substance.